

The H.E. Jackson Engineering range of Slasher Mowers combine toughness and effectiveness in a single package. Built for grass cutting and field slashing under all conditions, this is the implement you want behind your tractor when the going gets tough. Available in graded mild steel for inland or 3CR12 Stainless steel for corrosive climates, our mower slashers are all fitted with Cat II Linkage Systems and underbody 4 blade rotary slasher on a square table. A rear mounted rubber curtain or steel trap provides superior safety protection from flying stones and the heavy duty gearbox is protected via a clutch slip Carden shaft.



## TECHNICAL SPECIFICATION

	RK 1500	RK 1800	RK 2000
Cut Swathe	1.500mm	1800m	2000mm
Cut Height	25 - 150mm	25 - 150mm	25 - 150mm
Offset	300mm	nil	nil
Blade number	4	4	4
Operating Power	> 35 kW	> 50 kW	> 65 kW
Gearbox	45 kW	60 kW	78 kW
Construction	6mm S355J	6mm S355J	6mm S355K
Running Skids	8mm X 65mm	5mm X 65mm	6mm X 80mm
Weight	470 kg	519 kg	560 kg
Garden Shaft	Heavy Duty with Safety Clutch		



Kanengo Industrial, Area 28/Plot 91, Lilongwe, Malawi



[www.hejackson.com](http://www.hejackson.com)

[paul@hejackson.com](mailto:paul@hejackson.com) | [arie@hejackson.com](mailto:arie@hejackson.com)